

# EIC eRD102: Dual-Radiator RICH

Marco Contalbrigo – INFN Ferrara

---

EIC DAC Meeting - 19<sup>th</sup> October 2022

---

# The dRICH Project

Compact cost-effective solution for particle identification in the high-energy endcap at EIC




BA, BO, CS

CT, FE, GE,

LNF, LNS, RM1,

SA, TO, TS




NISER



p: 41 GeV, 100 to 275 GeV

p/A beam



e beam






e: 5 GeV to 18 GeV

The dual-radiator RICH has been a common reference in the forward region since EIC Yellow Report Important connections & synergies with other targeted EIC R&D (eRD102, eRD110, eRD109, ....)

# Dual Radiator RICH @ EIC

**Two main challenges**

**: cover wide momentum range 3 - 60 GeV/c  
work in high ( $\sim 1\text{T}$ ) magnetic field**



**dRICH: effective solution, part of EIC reference detector**

Radiators: **Aerogel** ( $n_{\text{AERO}} \sim 1.02$ ) + **Gas** ( $n_{\text{C}_2\text{F}_6} \sim 1.0008$ )  
extensive volume + focalization

Detector: **0.5 m<sup>2</sup>/sector**, **3x3 mm<sup>2</sup> pixel**  $\rightarrow$  **SiPM option**  
detector box outside acceptance

**Phase Space:**

- Polar angle: 5-25 deg
- Momentum: 3-60 GeV/c

# Risk Mitigation

## **Performance: Obtain an effective optics/resolution within EPIC constraints**

- ✓ Benchmark propose solutions with a prototype
- ✓ Simulate the non-trivial geometry (extended gas volume, field map)
- ✓ Study structure and services
- ✓ Interplay with other detectors (tracking, PID, material budget)

## **Photodetector: Realize a suitable (magnetic tolerant) photon detection plane**

- ✓ Study dark rate and radiation damage mitigation for SiPM
- ✓ Implement a streaming readout chain (ALCOR ToT)
- ✓ Contribute to LAPPD development in parallel
- ✓ Prototype a suitable detector plane (SiPM + DAQ with integrated cooling)

## **Aerogel: Validate aerogel manufacturers alternative to Russia**

- ✓ Characterization campaign for unprecedented aerogel with  $n=1.02$
- ✓ Investigate ASPEN interest and capability in optical aerogel
- ✓ Work with Aerogel Factory for customized aerogel (transparency, dimensions,...)

## **Gas: Search alternatives to greenhouse gases**

- ✓ Study mechanics of a pressurized vessel

## **Mirrors: Validate composite mirrors and structure materials**

- ✓ Validate the new cost-effective manufacturing procedure with CMA
- ✓ Study mirror support and alignment
- ✓ Study mechanics of the full-scale detector

✓ Well structured

✓ Ongoing

✓ Being started

Goal: Technical solution identification, specs definition, risk mitigation, cost assesement

## **FY22: Initial assessment on dRICH prototype based on the first test beams (12/22)**

- ✓ Basic prototype commissioning with beam in Fall 2021
- ✓ Upgrade in alignment, timing, beam instrumentation reading, services
- ✓ Second test-beam campaign in Fall 2022
- ✓ Detailed analysis vs simulations

## **Realistic implementation of dRICH into EIC detector (02/23)**

- ✓ Full simulation chain available within EPIC
- ✓ Realistic geometry under study
- ✓ Optical model of components being revisited
- ✓ Patter recognition and PID in conjunction with other detectors

## **Suitable detector plane for the dRICH prototype (03/23)**



- ✓ Candidate sensors identified with 2021 irradiation and annealing campaign
- ✓ ALCOR v2 submitted (better dynamical range and rate sustainability)
- ✓ Cooling scheme under study
- ✓ Electronic stack and mechanics design

# dRICH Prototype


Test beam @ PPE158 - SPS

September 2022

Refined alignment tools and procedure




Beam information: time and Cherenkov tagging




# Prototype Time Analysis


Hit start and End - Duration > 35




Hit duration - 2




Hit correlation




Trigger



Coincidence peak - 1





Δ time not calibrated - trigger time Vs Channel - 2



# Prototype Cherenkov Analysis

Preliminary results: Two radiators with 180 hadron beam with reference readout







# Prototype Radiator Interplay

Test at 50 GeV mixed hadron beam with tagging by beam instrumentation (3x gas Cherenkov)

Single particle radius - Gas




Single particle radius - Aerogel




# dRICH Gas

Scan the mirror position to align the focal plane on the sensor surface

Radius - Gas




Sigma - Gas :  $z_{\min} = 84.42$



# dRICH Aerogel

Chromatic dispersion measured with the dRICH prototype and optical filters selecting the wavelength range



Quantify the largest expected contribution to the Cherenkov angle resolution

Can be used to derive a general relationship with aerogel density based on a quartz+air mix model

Goal: Technical solution identification, specs definition, risk mitigation, cost assesement

## **FY22: Initial assessment on dRICH prototype based on the first test beams (12/22)**

- ✓ Basic prototype commissioning with beam in Fall 2021
- ✓ Upgrade in alignment, timing, beam instrumentation reading, services
- ✓ Second test-beam campaign in Fall 2022
- ✓ Detailed analysis vs simulations

## **Realistic implementation of dRICH into EIC detector (02/23)**

- ✓ Full simulation chain available within EPIC
- ✓ Realistic geometry under study
- ✓ Optical model of components being revisited
- ✓ Patter recognition and PID in conjunction with other detectors




## **Suitable detector plane for the dRICH prototype (03/23)**

- ✓ Candidate sensors identified with 2021 irradiation and annealing campaign
- ✓ ALCOR v2 submitted (better dynamical range and rate sustainability)
- ✓ Cooling scheme under study
- ✓ Electronic stack and mechanics design



# dRICH Simulations

C. Chatterjee @ RICH 2022

## ECCE simulation






## ATHENA simulation



## October Production Readiness: Simulation

**Ready!**

- Geometry consistent with menagerie
- Optics as good as ATHENA was







## Two “modules” for reconstruction:

- ◆ Standalone Indirect Ray Tracing (IRT) library – **Ready!**
- ◆ Bindings of IRT to Reconstruction Framework
  - 🔧 Working well, but with “**scaffolding**”:
- For a full campaign, we need to take down the scaffolding, and bind to EICRecon (in progress...)

## Reconstruction: Indirect Ray Tracing

Points: reconstructed Cherenkov Angle  
Curves: expected Cherenkov angle



Goal: Technical solution identification, specs definition, risk mitigation, cost assesement

**FY22: Initial assessment on dRICH prototype based on the first test beams (12/22)**

- ✓ Basic prototype commissioning with beam in Fall 2021
- ✓ Upgrade in alignment, timing, beam instrumentation reading, services
- ✓ Second test-beam campaign in Fall 2022
- ✓ Detailed analysis vs simulations

**Realistic implementation of dRICH into EIC detector (02/23)**

- ✓ Full simulation chain available within EPIC
- ✓ Realistic geometry under study
- ✓ Optical model of components being revisited
- ✓ Patter recognition and PID in conjunction with other detectors

**Suitable detector plane for the dRICH prototype (03/23)**




- ✓ Candidate sensors identified with 2021 irradiation and annealing campaign
- ✓ ALCOR v2 submitted (better dynamical range and rate sustainability)
- ✓ Cooling scheme under study
- ✓ Electronic stack and mechanics design



# Photo-Sensor Program

## Study solutions for single-photon detection within strong B-field

SiPM program: selection among various candidates  
R&D dark count mitigation



INFN: sensors, instrumentation, prototyping




LAPPD program

Test & guide developments @ Incom




INFN: rent, instrumentation

# SiPMs




R. Preghenella @ RICH2022



# SiPM Detector Plane

Hamamatsu S13361-3050




MPPC under procurement

ALCOR chip (high-rate ToT architecture) in streaming mode


- 50 ps time bin
- 500 kHz rate per channel
- cryogenic compatible

ALCOR v2 submitted for production


ALCOR chip



PCB with flex cable connection



Integrated Cooling



Streaming readout



FY23 funds



# dRICH Aerogel



Existing facility to study detailed radiator optical properties and alternatives

## Aerogel:

Safe handling and characterization (refractive index, surface planarity, forward scattering)

## Interplay between radiators:

UV filters, refractive index optimization



INFN 2023: Funds for new samples

**Aerogel Factory:** negotiate production of large

goals: study reproducibility

1<sup>st</sup> batch: 1.0206, 1.0206, 1.0199, 1.0204

2<sup>nd</sup> batch: 1.0201, 1.0207, 1.0210, 1.0218

**Goal: negotiate large (20x20 cm<sup>2</sup>) tiles with ALICE**

**ASPEN:** initial contacts with CUA (Tanja Horn)


**Goal: obtain few samples at 1.02**

**FY23  
funds**


# dRICH Mirrors

INFN 2023: funds for a CFRP mirror demonstrator



Surface Quality



Pointlike source image



Shack-Hartmann sensor




FY23  
funds




# dRICH Mechanics


INFN 2032: funds for a composite material study (targeted to over-pressure case)



Contacts re-initiated with BNL and JLab for engineering support



$$\sigma_{\max} = 142 \text{ MPa}$$



$$\Delta z_{\text{dir}} = +0 / - 0.21 \text{ cm}$$

Static structural Study @BNL

FY23 funds

## **FY23: Initial characterization of realistic mirror and aerogel components (02/23)**

- ✓ Optical laboratory being refurbished (spectrophotometer, lasers, cameras)
- ✓ Alternative components procurement
- ✓ Targeted R&D being discussed with the manufacturers
- ✓ Extended measurement campaign being organized

## **Projected performance of the baseline detector as integrated into EPIC (06/23)**

- ✓ Develop pattern recognition
- ✓ PID algorithm in conjunction with other detectors
- ✓ Validation with benchmark reactions
- ✓ Massive simulation campaign

## **Assessment of the dRICH prototype performance with the EIC-driven detection plane (10/23)**

- ✓ Prototype adaptation to the new detection plane
- ✓ Upgrade of the services (~1k channels DAQ, cooling, power lines)
- ✓ Test temperature control and in situ-annealing
- ✓ New test-beam campaign

**FY24/FY25:** specs definition, targeted eRD109/110 developments integration, TDR preparation

# Conclusions

Ongoing effort for the development of a forward RICH detector for particle identification at EIC

Cost-effective compact solution for hadron PID in EIC forward region in a wide kinematic range

Activity plan is organized following the EIC Critical-Decision timeline

## **R&D activity on innovative aspects with synergies with LHC (ALICE) and other EIC eRD**

**Prototyping and test-beam campaigns** to address crucial PID aspects at EIC

### **Optimized and alternate radiators**

Aerogel of medium refractive index and high transparency, noble gas at high pressure

**Novel cost-effective single-photon detector solution** to be operated in high magnetic field

SiPM post-irradiation characterization and imaging tests (+LAPPDs)

### **Readout**

Alternate ToT architecture (ALCOR chip)

### **Cooling, support structure, pressurized vessel**

US technical support is essential



# dRICH Timeline

Year	Detailed tasks
2021	<ul style="list-style-type: none"> <li>• Development of basic prototype design, simulation and implementation</li> <li>• Optical components: First selection and tests</li> <li>• Basic prototype: Basic tracking, one choice per radiator, glass mirrors, reference readout</li> <li>• Beam Test 1: Proof of principle with reference detectors and readout , ideal beam</li> <li>• Import dRICH simulation into the supported EIC platforms</li> </ul>
2022	<ul style="list-style-type: none"> <li>• Analysis of the first test-beam</li> <li>• Refined prototype: refined components and readout, online reconstruction, precise tracking/alignment</li> <li>• Beam Test 2: Performance assessment with reference and custom detectors, hadron tagged beams</li> </ul>
2023	<ul style="list-style-type: none"> <li>• R&amp;D on cooling</li> <li>• EIC configuration engineering and integrated PID</li> <li>• Optical components refinement and cost reduction study (e.g. glass-skin mirror)</li> </ul>
2024	<ul style="list-style-type: none"> <li>• Component alternatives and optimization</li> <li>• Final prototype: various radiators, custom mirrors, gas system, optimized readout</li> <li>• Beam test 3: Performance assessment with optimized components</li> </ul>
2025	<ul style="list-style-type: none"> <li>• Engineering of cooling and services</li> <li>• Beam test 4: Contingency</li> </ul>

Assumed funding profile k\$.

	prototype	radiators	mirror	detector	personnel	technical	travel	total
FY23	10	20	20	20	100	10	10	190
FY24*	10	20	20	10	80	10	10	160
FY25*		20	20	10	60	10	10	130